

Ship To : ANAS AL MOREI
3068 OAK CREED RD
CHINO HILLS, CA 91709
Phone C: 407--34-6260
Phone H: 949--40-9226

Bill To : ANAS AL MOREI
3068 OAK CREED RD
CHINO HILLS, CA 91709
Phone C: 407--34-6260
Phone H: 949--40-9226

Line	Qty	Product Type	Product details	Unit Price	Total Price
1	1	Roller Shade	Room: Liv Rm A, Mount Type: Inside Mount, Width: 33 1/2, Length: 57 1/8, Fabric: London Light Filtering, Color: Hampton Beige RLOLF, Price Band: Coastline Roller 3, Top Treatment: Cassette 100, Cassette 100 Color Option: White, Roll Type: Regular Roll, Control Type: Chain, Chain Type: Plastic Chain, Plastic Chain Color Option: White, Control Side: Left, Bottom Rail: Sealed Hembar Pocket, Special Instructions: MOTOR READY	160.20	160.20
2	1	Roller Shade	Room: Liv Rm B, Mount Type: Inside Mount, Width: 57 3/8, Length: 75 1/8, Fabric: London Light Filtering, Color: Hampton Beige RLOLF, Price Band: Coastline Roller 3, Top Treatment: Cassette 100, Cassette 100 Color Option: White, Roll Type: Regular Roll, Control Type: Chain, Chain Type: Plastic Chain, Plastic Chain Color Option: White, Control Side: Right, Bottom Rail: Sealed Hembar Pocket, Special Instructions: MOTOR READY	254.00	254.00
3	1	Roller Shade	Room: Liv Rm C, Mount Type: Inside Mount, Width: 33, Length: 57 3/8, Fabric: London Light Filtering, Color: Hampton Beige RLOLF, Price Band: Coastline Roller 3, Top Treatment: Cassette 100, Cassette 100 Color Option: White, Roll Type: Regular Roll, Control Type: Chain, Chain Type: Plastic Chain, Plastic Chain Color Option: White, Control Side: Right, Bottom Rail: Sealed Hembar Pocket, Special Instructions: MOTOR READY	160.20	160.20
4	1	Roller Shade	Room: Liv Rm D, Mount Type: Inside Mount, Width: 33 1/4, Length: 57 1/4, Fabric: London Light Filtering, Color: Hampton Beige RLOLF, Price Band: Coastline Roller 3, Top Treatment: Cassette 100, Cassette 100 Color Option: White, Roll Type: Regular Roll, Control Type: Chain, Chain Type: Plastic Chain, Plastic Chain Color Option: White, Control Side: Left, Bottom Rail: Sealed Hembar Pocket, Special Instructions: MOTOR READY	160.20	160.20

