



## LET'S ROLL

### Introducing Our Express Roller Shades Program

High quality, single or dual-style manual roller shades in 10 days\*. That's our promise. We've carefully curated an Express Roller Shades program specifically designed to meet the needs of hotels and businesses looking for quick-turn, beautiful, yet economical manual roller shade options they can install themselves.

*\*The 10-day Express production time applies to orders of 50 roller shades or less. For orders with a quantity of more than 50 shades, please connect with your sales representative to advise on production turnaround times.*

## How It Works

Download the Express Roller Shade order form. Select your fabric type and color from the collections below. Complete the order form and submit to [sales@readwindow.com](mailto:sales@readwindow.com). You will receive a confirmation and next steps email directly from Culp Hospitality/Read Window Products.

[GET STARTED](#)



## ROLLER SHADE FABRIC OPTIONS & SPECIFICATIONS

### Spectrum – Blackout Shades

Spectrum Blackout combines the functionality and durability of a typical solar screen with the privacy of a 100% blackout fabric.

The **unique formulation of the yarn** eliminates the need for a blackout coating thereby keeping the blackout fabric the same on both sides and making it highly suitable for open roll systems. Featuring Sanitized®, Spectrum Blackout inhibits the development of bacterial odors as well as the growth of mold and mildew on your fabric.

**Easy to install and clean**, Spectrum Blackout provides a practical solution for any hospitality, residential or commercial interior space.

#### AVAILABLE COLORS



Ice

Barley

Alloy

Graphite

Black



#### SPECIFICATIONS AT A GLANCE

**Composition:** 25% Polyester, 75% PVC

**Weight:** 16.96 oz/yd<sup>2</sup> (575g/m<sup>2</sup>)

**Thickness:** 0.027in (.69mm)

**Light Fasting:** Grade 4 (AATCC 16)

**Width:** 118" (3m)

**Fire Classification:** NFPA 701

#### CLEANING

Lightly vacuum or wipe with dry cloth to remove dust. Spot clean with clean white pencil eraser or gently wipe with warm soapy water and damp sponge. If wet, leave shade down to dry completely. Avoid solvents or test them in inconspicuous area first.

#### CERTIFICATIONS





## 5% OPENNESS

# Spectrum – Light Filtering Shades

Spectrum Light Filtering roller shade fabric is a lightweight 2x1 basketweave textile that has been manufactured with the health and safety of customers in mind making it suitable for all hospitality, residential and commercial applications.

Spectrum features Sanitized® which inhibits the development of bacterial odors as well as the growth of mold and mildew. This unique antimicrobial hygiene feature enhances the performance of your shades for comfort and peace of mind.

## AVAILABLE COLORS



White

Barley

Alloy

Graphite

Black

## SPECIFICATIONS AT A GLANCE

**Composition:** 26% Polyester, 74% PVC

**Openness:** Average 5%

**Width(s):** 98.4" (2.5m), 118" (3m)

**Weight:** 14.01 oz/yd<sup>2</sup> (475 g/m<sup>2</sup>)

**Fire Classification:** NFPA 701

**Fungal/Bacterial Resistance:** ASTM E2180, G21

**Acoustical Performance:** NRC 0.20 | SAA 0.20

## CLEANING

Lightly vacuum or wipe with dry cloth to remove dust. Spot clean with clean white pencil eraser or gently wipe with warm soapy water and damp sponge. If wet, leave shade down to dry completely. Avoid solvents or test them in inconspicuous area first.

## CERTIFICATIONS



## TIPS & TECHNIQUES

### How to Measure

Roller shades add both function and style to your windows, but getting the measurements just right is critical to a flawless installation. In this step-by-step guide, we'll walk you through the simple process of measuring your windows like a pro, ensuring a perfect fit.

#### QUICK MEASURING TIPS

### Do-It-Yourself Installation

This step-by-step guide will walk you through the process of installing our Express Roller Shades in your property. The guide covers preparing the installation area, tips on where to begin and detailed instructions on how to securely mount the shades and tensioning device.

#### DIY INSTALLATION GUIDE



Questions? Contact Your Sales Representative Today  
or contact us at [sales@readwindow.com](mailto:sales@readwindow.com).

